

## Additional web-service operations since v5.1

### ▼ [Content](#)

## Additional web-service operations since v5.1

### createSubsidiary operation

#### General

With this operation, the agencies would be able to create new subsidiaries in the system.

#### Request

createSubsidiary request is consisted of following elements:

- path – mandatory element (dossier-specific ids for path and its children elements should not be set)
- rulmPairId – mandatory element (this element should be provided in order PCS to resolve to which dossier subsidiary should be added)

#### Response

createSubsidiary operation returns a response consisted of the following:

- status – description for the response. The list of error codes can be found in the Appendix A

### makeObservations

#### General

makeObservation operation exposed in PCS IP creates new, formatted (per the defined convention) comment in the dossier, based on the user provided input.

#### Request

makeObservation request is consisted of the following elements:

- newObservation element which is consisted of the following
  - imIds – a mandatory list of IM agencies ids in the dossier which are influenced by the observation (the exact agencies ids can be found in the dossier xml)
  - imPathInfo (optional element)




- pathId – IM path id for which the observation is about (the exact path id can be found in the dossier xml)
- startingOperationPointId - operation point for which the observation is about. Should belong to entered pathId.
- endingOperationPointId - operation point for which the observation is about. Should belong to entered pathId.
- observationReasons – an optional element that indicates the reason for observation. In order to get id for observation reason you can use helper operation: getObservationTypes.
- comment - an optional element, for further description of the objection
- isJustified – an optional element that indicates whether the objection is justified
- dossierId – mandatory element (this element should be provided in order PCS to resolve to which dossier the observation should be added.)

#### Response

makeObservation operation returns a response consisted of the following

- id – id of the created observation
- status – description for the response. The list of error codes can be found in the Appendix A. If everything went ok, the return code is:
  - 100 - SUCCESS

#### ▼ Print

-  [Printer-friendly version](#)
-  [Send by email](#)
-  [PDF version](#)

#### ▼ Details

**State:** Published  
**Topic:** [PCS Interface](#)  
[Integration Platform](#)  
**Area:** [Technical](#)  
**Release:** [5.x](#)  
**Company**      [All](#)  
**Type:**  
**Keywords:** [pcs ip](#)  
[webservice](#)  
[handbook](#)

#### ▼ Translations

**No translations**

---

**Source URL:** <https://cms.rne.eu/pcs/pcs-documentation/additional-web-service-operations-v51>